

AM II-16/32

Aerosol Manifold



The AM II manifold offers advanced features for sequentially monitoring aerosol contamination at multiple locations with a fixed particle counter. The AM II is ideal for trend analysis and cleanroom verification when continuous monitoring is not needed.

COMPATIBILITY

- Lasair® II or Lasair III particle counters, or IsoAir® PLUS particle sensor

BENEFITS

Cost Effective

- Most economical monitoring of fixed points at timed intervals
- Low cost per sample location
- Monitors a much larger area than a fixed particle counter
- Ethernet communications to facility monitoring system

Flexible

- Easily programs a sampling routine, for either simple or complex sequences
- Automatically changes sampling recipe upon receiving alarm or external signal
- Large coverage area: each sample point can be up to 125 ft away

Rapid and Accurate Measurements

- Patented flow control ensures the manifold properly compensates for manifold pressure drop, eliminating systematic particle undercounting of up to 15%
- Maintains constant flow (nominal 3 CFM) at each sample location to minimize gravitational particle settling
- With isokinetic sampling probes, captures particles at same velocity as sample air, preventing distortion in particle size relationships

FEATURES

- Multiplexed monitoring of up to 32 locations with a single particle counter
- Controlled by Facility Net or Pharmaceutical Net software
- Programmable recipes and sample point sequences
- Assembly designed to eliminate contamination from valves
- Alarm for low vacuum; automatic shut-off for pump overheating

APPLICATIONS

- Facility monitoring
- Monitoring large minienvironments
- Cleanroom verification and trend analysis

AM II-16/32

Aerosol Manifold

Specifications

Manifold System	AM II-16	AM II-32
Sample ports	Max. 16, Min. 10	Max. 32, Min. 22
Operating range	Use in locations ISO 8 (Class 100,000) or cleaner 0.1 to 0.3 µm particle counters: Use to simultaneously monitor ISO 3, 4, 5, and 6 (Classes 1, 10, 100, 1000) 0.5 to 5.0 µm particle counters: Use to simultaneously monitor ISO 5, 6, 7, and 8 (Classes 100, 1000, 10,000, 100,000)	
Manifold Pump		
Pumps required	1 (single-phase)	1 (3-phase)
Flow rate	> 100 ft³/min	> 150 ft³/min
Safety provision	Automatic pump shutoff	Automatic pump shutoff
Power	105 – 125 VAC, 60 Hz or 220-240 VAC, 50 Hz 10.9 Amp, single-phase	415 – 480 VAC, 60 Hz 5.0 Amp, 3-phase
Dimensions (l, w, h); weight	10.6 x 11.2 x 16.2 in (27 x 28 x 41 cm); 42 lb (19 kg)	16.7 x 15.0 x 20.0 in (47 x 38 x 51 cm); 75 lb (34 kg)
Manifold Module		
Flow rate	1.5 – 3 CFM per port (nominal)	
Purge time (between ports)	15 sec recommended	
Cross talk (from other ports)	< 0.1%	
Sample tubing	Bev-A-Line XX® 1/2" OD, 3/8" ID (part # MI-153)	
Sample tubing length and bend	25' – 125' per port. Minimum 9" radius for Bev-A-Line XX®	
Fittings provided	16 (or 32) self-locking, 1/2" OD, Legris® (L-Legris) fittings	
Vacuum required	30" – 55" water	
Mounting orientation	Vertical; wall mounting bracket included	
Power	Provided by control box via controller cable	
Dimensions (l, w, h); weight	13.5 x 13.5 x 15.3 in (34 x 34 x 39 cm); 13.5 lb (6.1 kg)	
Control Box		
Controlling software	Facility Net/Pharmaceutical Net (purchased separately)	
Communications protocol	Ethernet	
Firmware setup modes	RS-232, Telnet	
Ethernet outlets (2)	Network/Primary sensor	
Automatic alarm	Inadequate manifold vacuum	
Mounting	Vertical or horizontal; built-in mounting holes	
Power	105 – 125 VAC, 60 Hz; 220 – 240 VAC, 50 Hz	
Dimensions (l, w, h); weight	7 x 8.5 x 12.5 in (18 x 22 x 32 cm); 11.5 lb (5.2 kg); painted steel box	
System operating conditions	Temperature: 59 – 95° (15 – 35 °C); Humidity: non-condensing	

System Components Included:
Manifold module, control box, pump, operations manual, power cord, control cable, wall-mounting bracket, monitor exhaust tubing, pressure sensor tubing, pump tubing, and clamps.

Not included:
Particle counter/sensor, ISPs, sample tubing, communications cables (manifold to counter/sensor), PC, Facility Net or Pharmaceutical Net software.

System Components Included:

Manifold module, control box, pump, operations manual, power cord, control cable, wall-mounting bracket, monitor exhaust tubing, pressure sensor tubing, pump tubing, and clamps.

Not included:

Particle counter/sensor, ISPs, sample tubing, communications cables (manifold to counter/sensor), PC, Facility Net or Pharmaceutical Net software.

Lasair® and IsoAir® are registered trademark of Particle Measuring Systems, Inc.
All other trademarks are the property of their respective owners.
Particle Measuring Systems, Inc. reserves the right to change specifications without notice.
© 2018 Particle Measuring Systems, Inc. All rights reserved.

HEADQUARTERS

5475 Airport Blvd
Boulder, Colorado 80301 USA
T: +1 303 443 7100, +1 800 238 1801

Instrument Service & Support
T: +1 800 557 6363

Customer Response Center
T: +1 877 475 3317
E: info@pmeasuring.com

www.pmeasuring.com
info@pmeasuring.com



**PARTICLE
MEASURING
SYSTEMS®**
a spectris company

GLOBAL OFFICES

AUSTRIA
T: +43 512 390 500
E: pmsaustria@pmeasuring.com

BENELUX
T: +32 10 23 71 56
E: pmsbelgium@pmeasuring.com

BRAZIL
T: +55 11 5188 8227
E: pmsbrazil@pmeasuring.com

CHINA
T: +86 21 6113 3600
E: pmschina@pmeasuring.com

FRANCE
T: 33(0)1 60 10 32 96
E: pmsfrance@pmeasuring.com

GERMANY
T: +49 6151 6671 632
E: pmsgermany@pmeasuring.com

ITALY
T: +39 06 9053 0130
E: pmsrl@pmeasuring.com

JAPAN
T: +81 3 5298 8175
E: pmsjapan@pmeasuring.com

KOREA
T: +82 31 286 5790
E: pmskorea@pmeasuring.com

MEXICO
T: +52 55 2271 5106
E: pmsmexico@pmeasuring.com

NORDIC
T: +45 707 028 55
E: pmsnordic@pmeasuring.com

PUERTO RICO
T: +1 787 718 9096
E: pmspuertorico@pmeasuring.com

SINGAPORE
T: +65 6496 0330
E: pmssingapore@pmeasuring.com

SWITZERLAND
T: +41 71 987 01 01
E: pmsswitzerland@pmeasuring.com

TAIWAN
T: 886-3-5525300 Ext: 301
E: pmstaiwan@pmeasuring.com